

multiflex Basic P7/multiflex plus Basic P7



**Where size matters:
The multiflex P7 is available
up to 15 m.**

If the standard multiflex modular system does not have the required size, the multiflex P7 series offers the perfect solution: With side heights of 2.30 m or 2.50 m and a tried and tested truss-distance of 3 m, the P7 modular system is available in the sizes 6, 9, 12 and 15 m. The emphasis of development was on the side height of 2.30 m enabling all multiflex units of the P9 series to be joined in a

professional manner. System cassette wall elements of hard-PVC or glass are available with a side height of 2.50 m. The spindle-fix roof tensioning system used with the Plus Version stops the valance flapping in the wind and offers additional rain protection in the eave area.

Highly efficient: Materials such as purlins, side curtains or system flooring from the multiflex P9 modular system can also be used in the P7 system. This makes the multiflex P7 the ideal solution for tent sizes above 10 m.



multiflex Basic P7/multiflex plus Basic P7

Technology

Easy to transport, assemble and dismantle, store and clean. Assembly with and without system cassette flooring possible.

Frame

- Trusses of extruded 4-groove aluminium hollow profiles
- Curtain tubes (Standard Version)
- Curtain tubes, eave purlins and gable beams made of aluminium
- Integrated curtain groove in eave purlins and gable beams (Plus Version)
- Frame for system cassette wall elements of hard-PVC or glass (Plus Version with side height of 2.50 m)
- Supporting device for ClipTex® system elements (Plus Version)
- All aluminium components are technically anodized
- All cables are PVC-coated, preventing blackening stains on contact with the covers
- All steel parts are hot-dip galvanized according to DIN EN ISO 1461
- Completely maintenance-free frame
- Adjustable base plates for compensation of unlevel surfaces
- Structural lengths in 3 m increments
- Structures may be joined to form larger areas
- With 2.30 m side height, precise joining of multiflex P9 and P7 possible





Covers

- Textile covers made of polyester fabric, coated with PVC on both sides, weight approx. 630 g/m²
- Translucent roof covers for daylight conditions inside the tent
- Time-saving expander tensioning system for fixation of roof covers (Standard Version)
- Secure fixing of the valance using the spindle-fix roof tensioning system stops valance flapping in the wind and offers additional rain protection in eave area (Plus Version).
- Flame-retardant according to DIN 4102, fire class B1
- For side and gable curtains, quality zippers: Rapid opening and closing

- Standard fabric colour white; other colours available on request
- Side curtains with windows in several attractive designs.
- System cassette wall elements of hard-PVC or glass, height 2.50 m (Plus Version)
- System wall elements ClipTex® (Plus Version)

Optional accessories

- Spliced beams for 12 m and 15 m widths
- Widths up to 9 m available on request. Portal beam for free access at all points. No disturbing cables/braces
- Roll-up entrances
- Aluminium doors, double-wing
- Gables with ventilations

- Light impermeable roof for longer service life and reduction of temperature in the tent. Weight about 850 g/m²
- Roof covers and side curtains of transparent foil
- Covers with individual texts or motifs
- Cassette flooring
- Ramps at entrances and exits
- Lining decoration for roof and walls
- Packing bags
- Assembly tools



Dimensions

Type		6/230 - 250	9/230 - 250	12/230 - 250	15/230 - 250
Width	(m)	6.07	9.07	12.07	15.07
Eave height	(m)	2.29/2.49	2.29/2.49	2.29/2.49	2.29/2.49
Ridge height	(m)	3.39/3.59	3.94/4.14	4.48/4.68	5.03/5.23
Truss-distance	(m)	3.00	3.00	3.00	3.00
Extension increment	(m)	3.00	3.00	3.00	3.00
Minimum structure length	(m)	6.00	6.00	12.00	12.00
Roof slope	(degrees)	20	20	20	20
Truss profile	(mm)	120 x 48	120 x 48	120 x 48	120 x 48
Longest component	(m)	3.525	4.870	6.470	8.070
Gable pole	(pcs)	1	2	3	4
Intermediate purlins	(pcs)	0	1	1	2
Expander roof tensioning system		x	x	x	x
Spindle-fix roof tensioning system*		x	x	x	x

* only Plus Version

Headoffice Heilbronn
 Losberger GmbH
 Fürfeld · Gottlieb-Daimler-Ring 14
 74906 Bad Rappenau · Germany
 Phone: +49 7066 980-0
 Fax: +49 7066 980232
 E-Mail: losberger@losberger.com
 www.losberger.com

Subsidiaries and Agencies Worldwide.

NOTE: Subject to alterations in the interest of product improvement in line with state-of-the-art technology progress.

LOSBERGER